

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 09-093216

(43)Date of publication of application : 04.04.1997

(51)Int.Cl.

H04J 11/00
H04L 27/36
H04L 27/20
H04N 5/40
H04N 7/08
H04N 7/081

(21)Application number : 07-245911

(71)Applicant : SONY CORP

(22)Date of filing : 25.09.1995


(72)Inventor : MIYATO YOSHIKAZU
MOMOSHIRO TOSHIHISA
ITO YASU
IKEDA YASUNARI

(54) DATA TRANSMITTER AND DATA TRANSMISSION METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To improve more the quality of an OFDM modulation signal.

SOLUTION: A signal point transmitter 14 allocates a signal point $Z_{k,l}$ in a QPSK modulation circuit 18 to parallel data S100 inputted from an S/P conversion circuit 100 by changing an amplitude so as to compensate an aperture effect of a communication transmission line and each section after an IFFT circuit 104 onto a modulation signal S20. D/A converter circuits 1061, 1062 and LPF circuits 1081, 1082 convert complex number data $z_{k,m}$ into analog form and eliminate an undesired harmonic component to generate transmission signals S1061, S1062. The QPSK modulation circuit 18 adopts the QPSK modulation system to generate a modulation signal S18 at an intermediate frequency band. A transmission circuit 20 converts the modulation signal S18 into a modulation signal S20 at a carrier frequency band of a communication transmission line to send it.



LEGAL STATUS

[Date of request for examination] 20.12.2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3525576

[Date of registration] 27.02.2004

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]